

Specification

Sensor	OPP06
Dimensions	54 x 74 x 82.6 mm (With stand) 27.4 x 40.5 x 73.7 mm (Without stand)
Image Size	248 x 292 pixels
Resolution	500 DPI
Interface	USB 1.1 / 2.0 High / Full speed
Image Acquisition Time	Full Speed : Avg. 500 msec. High Speed : Avg. 300 msec.
Operating Temperature	-20~60°C
Humidity	< RH 90%
Power Source	USB BUS Power
OS	Windows 2K/XP/Vista/7, Windows Server 2003/2008, Linux Kernel 2.6 or later
Auto-On	○
Certificate	KC, UL, CE, FCC

Features

- **USB Connection**
 - USB 2.0 compatible interface, plug and play device
 - Supports multiple devices handling
- **Advanced Optical Technology**
 - Sensor resistant to scratches, impact, vibration and electrostatic shock
- **Superior Matching Engine**
 - 1st in FVC(Fingerprint Verification Competition)
 - Auto-on Function
- **International Standard Image Format and Interfaces**
 - WSQ compression
 - ISO 19794-2/4, ANSI378, NFIQ
- **High Quality Image Capturing**
- **Strong Performance for Wet / Dry Finger**

Development Kit >> eNBSP SDK

- * Provides optimal APIs for fingerprint Capture recognition software development
- * Provides wizard for quick development
- * Sample source code for new application development
- * Includes all header and library files and full documentation for development and distribution
- * Multi fingerprint per user (Up to 10 templates)
- * World's most reliable fingerprint algorithm (Top rank 1 results in FVC)

Item	Specifications
OS	Windows 2000 / XP / 2003 / Vista / 7 , Linux Kernel 2.6.x
PC	Pentium III or higher
Development Language	VC++, VB, ASP, Delphi, .Net, and etc.
Encryption	SEED, AES128, AES256, TripleDES, and etc.
Supportable Device	Fingkey Hamster Series / Fingkey Mouse Series

Application



Computer Security



IT Solution (Groupware, etc.)



Health care System



Security of Bank and financial system



Password

Substitution for password



e-Commerce

Fingkey Hamster DX



eTOP Solution
P.O.Box. 111645, Abu Dhabi, U.A.E
Tel: (971) 2-650 3433 Fax: (971) 2-650 3553

eTOP Solution
P.O.Box. 488201, Dubai, U.A.E
Tel.: (971) 4-455 9007 Fax: (971) 4-455-3043